



HP Lubricants - Product Data Sheet



HYLUBE HDX MULTIGRADE 20W40 & 20W50

- HYLUBE HDX MG 20 W 40 & 20 W 50 ARE MULTIGRADE ENGINE OILS
- MEETS API CC/SC , US MILITARY MIL-L-2104B, IS:13656:1993 SPECIFICATION
- RECOMMENDED FOR USE IN ALL TYPES OF DIESEL & PETROL ENGINES
 - EXCELLENT ENGINE PROTECTION UNDER HIGH TEMPERATURES
 - GOOD ENGINE START UP UNDER COLD CONDITIONS
 - BETTER ALL-ROUND PERFORMANCE.

PROPERTIES	HYLUBE HDX MULTIGRADE 20 W 40	HYLUBE HDX MULTIGRADE 20 W 50
KINEMATIC VISCOSITY c St @ 40 DEG C	120	140
KINEMATIC VISCOSITY cSt @ 100 DEG C	14-16	17-19
VISCOSITY INDEX,MIN	110	110
FLASH POINT, (COC) C,MIN	200	200
POUR POINT, C , MAX	-21	-21
SULPHATED ASH,%WT,MAX	0.74	0.77
TBN ,mgKOH/g,MIN	4.05	4.05
COLOURX	RED	RED

APPROVED BY:

- M/s SWARAJ MAZDA
- M/s PUNJAB TRACTORS
- M/s HMT
- M/s EICHER
- M/s ESCORTS
- M/s BRITANNIA ENGG.LTD.
- M/s GUJRAT FORGIN

PRESS TO
RETURN



FOR FURTHER INFORMATION PLEASE CONTACT OUR NEAREST
REGIONAL OFFICE