



HP Lubricants - Product Data Sheet



HYLUBE MILCY 30,40,50

- HYLUBE MILCY 30,40,50 ARE SUPERIOR QUALITY, HEAVY DUTY DIESEL ENGINE LUBRICATING OILS
- MEETS API CD/SF , MIL-L-2104C,E-DL 3/SF + MACK T7 OF IS:13656 AND MACK T-7 ENGINE TEST REQUIREMENTS.
- RECOMMENDED FOR HEAVY COMMERCIAL VEHICLES, LIGHT COMMERCIAL VEHICLES,TRACTORS, DIESEL PASSENGER CARS AND JEEPS REQUIRING MONOGRADE OILS
 - EXTENDED TBN RESERVES
 - PREVENTS OIL THICKENING AND ENHANCES OIL LIFE
 - CONTROL OF CORROSIVE WEAR
 - EXCEPTIONAL THERMAL&OXIDATION STABILITY
 - PROLONGED ENGINE LIFE & ENHANCED DRAIN PERIOD
 - OUTSTANDING ENGINE CLEANLINESS

	30	40	50
KINEMATIC VISCOSITY cst @ 100C	10.3-11.5	13.5-15.2	17.5-24
VISCOSITY INDEX,MIN	95	95	95
FLASH POINT, (COC) C,MIN	215	215	220
POUR POINT, C , MAX	-6	-6	-6
SULPHATED ASH,%WT,MAX	1.6	1.6	1.6
TBN ,mgKOH/g,MIN	9.5	9.5	9.5

APPROVED BY:

- M/s FUJI, M/s ECEL, M/s GREAVES, M/s EICHER, M/sGUJARAT FORGINGS
- M/s TAFE, M/s ASHOK LEYLAND, M/s BAJAJ TEMPO, M/sVOLTAS LTD.
- M/s HMT, M/s VST TILLERS, M/s PUNJAB TRACTORS, M/sTELCO

PRESS TO
RETURN



FOR FURTHER INFORMATION PLEASE CONTACT OUR NEAREST
REGIONAL OFFICE