



HP Lubricants - Product Data Sheet



HYLUBE EXTRA 20W 40

- HULUBE EXTRA 20W 40 IS A PREMIUM MULTIGRADE ENGINE OIL DESIGNED TO MEET THE DEMANDING LUBRICATION REQUIREMENTS OF ALL MODERN DIESEL ENGINES.
- MEETS API CD/SF, MIL-L-2104C,E-DL 3 OF IS:13656:1993 AND MACK T-7 ENGINE TEST REQUIREMENTS.
- RECOMMENDED FOR ALL DIESEL ENGINES.
 - PREVENTS OIL THICKENING AND ENHANCES OIL LIFE
 - CONTROL OF CORROSIVE WEAR
 - EXCELLENT THERMAL & OXIDATION STABILITY
 - PROLONGED ENGINE LIFE & ENHANCED DRAIN PERIOD

KINEMATIC VISCOSITY cst @ 40 DEG C	118
KINEMATIC VISCOSITY cst @ 100 DEG C	14-15
VISCOSITY INDEX,MIN	110
FLASH POINT, (COC) C,MIN	200
POUR POINT, C , MAX	-21
SULPHATED ASH,%WT,MAX	1.51
TBN ,mgKOH/g,MIN	10.4

APPROVED BY:

- M/s ASHOKLEYLAND, M/s BEML
- M/s TAFE , M/s KCL
- M/s HM

**PRESS TO
RETURN**



**FOR FURTHER INFORMATION PLEASE CONTACT OUR NEAREST
REGIONAL OFFICE**