



# HP Lubricants - Product Data Sheet



## HYLUBE CDKC 20W 40

- HULUBE CDKC 20W 40 IS A MULTIGRADE ENGINE OIL OF OUTSTANDING PERFORMANCE SPECIALLY DEVELOPED FOR KIRLOSKAR CUMMINS
- MEETS API CD, MIL-L-45199B,E-DL 2 OF IS:13656
- RECOMMENDED FOR USE IN DIESEL ENGINES REQUIRING THIS LEVEL
  - EXCEPTIONAL THERMAL & OXIDATION STABILITY
  - OUTSTANDING VISCOSITY RELATED PERFORMANCE
  - PROLONGED ENGINE LIFE

<b>KINEMATIC VISCOSITY cst @ 100 deg C</b>	<b>14-15</b>
<b>VISCOSITY INDEX,MIN</b>	<b>110</b>
<b>FLASH POINT, (COC) C,MIN</b>	<b>200</b>
<b>POUR POINT, C , MAX</b>	<b>-21</b>
<b>SULPHATED ASH,%WT,MAX</b>	<b>1.46</b>
<b>TBN ,mgKOH/g,MIN</b>	<b>9</b>

**PRESS TO  
RETURN**



**FOR FURTHER INFORMATION PLEASE CONTACT OUR NEAREST  
REGIONAL OFFICE**