



# HP Lubricants - Product Data Sheet



## HYLUBE SHP 15W 40

- HYLUBE SHP 15W 40 IS A PREMIUM QUALITY “HIGH PERFORMANCE DIESEL ENGINE OIL”
- MEETS MB 228.3, VOLVO VDS2 & E-DL4 OF IS:13656-1993 SPECIFICATIONS
- RECOMMENDED FOR USE IN ALL NEW GENERATION DIESEL ENGINES.
  - EXCEPTIONAL THERMAL & OXIDATION STABILITY
  - OUTSTANDING VISCOSITY RELATED PERFORMANCE
  - LONG DRAIN PERIODS
- HYLUBE SHP 15W-40 HAS SUCCESSFULLY COMPLETED 45,000KMS DRAIN PERIODS AT LEADING STU'S

|                                       |              |
|---------------------------------------|--------------|
|                                       |              |
| <b>KINEMATIC VISCOSITY cst @ 100C</b> | <b>14-16</b> |
| <b>VISCOSITY INDEX, MIN</b>           | <b>125</b>   |
| <b>FLASH POINT, (COC) C, MIN</b>      | <b>200</b>   |
| <b>POUR POINT, C, MAX</b>             | <b>-24</b>   |
| <b>TBN ,mgKOH/g, MIN</b>              | <b>13</b>    |

### APPROVED BY:

- M/s MERCEDES BENZ, GERMANY
- M/s VOLVO, SWEDEN
- M/s SAME GREAVES

**PRESS TO  
RETURN**



**FOR FURTHER INFORMATION PLEASE CONTACT OUR NEAREST  
REGIONAL OFFICE**