



HP Lubricants - Product Data Sheet



HP AUTOLUBE 30,40

- HP AUTOLUBE 30,40 ARE SPECIALLY DEVELOPED ENGINE LUBRICANT CUM RUNNING IN OILS CONTAINING ADDITIONAL CORROSION PROTECTION
- RECOMMENDED FOR ALL ENGINES AS RUNNING OIL, PRESERVATIVES & FIRST FILL OILS
 - PROVIDES PROPER RUNNING-IN OF ENGINE
 - PROTECTS ENGINE COMPONENTS AGAINST RUST AND CORROSION
 - CONTAINS REQUIRED DETERGENCY & DISPERSANCY
 - MEETS MIL-L-2104 B SPECIFICATIONS WITH ADDITIONAL CORROSION PROTECTION

	30	40
KINEMATIC VISCOSITY <i>est</i> @ 100C	9.6-12.4	14-16
VISCOSITY INDEX,MIN	90	90
FLASH POINT, (COC) C,MIN	210	210
POUR POINT, C , MAX	0	0
SULPHATED ASH,% WT,MAX	1.2	1.2
TBN ,mgKOH/g,MIN	7.5	7.5
CORROSION Cu STRIP @ 100 C FOR 3Hrs , MAX	1	1
DB CORROSION TEST		
CORROSION RESISTANCE NUMBER,MIN	90	90
STAINING/DISCOLOURATION,MAX	NONE	NONE

APPROVED BY :
M/s TELCO
M/s HM
M/s GUJRAT FORGINGS

PRESS TO
RETURN



FOR FURTHER INFORMATION PLEASE CONTACT OUR NEAREST
REGIONAL OFFICE