



HP Lubricants - Product Data Sheet



HP AUTOPRUN T 120

- HP AUTOPRUN T120 IS A SPECIALLY DEVELOPED TRIPLE ACTION OIL FOR USE IN PETROL AND DIESEL ENGINES DURING RUNNING IN OPERATION, TRANSPORTATION , STORAGE AND DURING NORMAL RUNNING
- RECOMMENDED FOR ALL ENGINES AS RUNNING IN OIL, PRESERVATIVE & FIRST FILL OILS
 - PROVIDES PROPER RUNNING –IN
 - PROTECTS ENGINES COMPONENTS AGAINST RUST AND CORROSION DURING TRANSPORTATION OR LONG STORAGE EVEN UNDER ADVERSE CONDITIONS SUCH AS DURING SEA VOYAGE
 - CONTAINS REQUIRED DETERGENCY & DISPERSANCY
 - MEETS MIL-L-2104 A WITH ADDITIONAL CORROSION PROTECTION

KINEMATIC VISCOSITY cst @ 40C	108-120
KINEMATIC VISCOSITY cst @ 100C	9.6-12.4
VISCOSITY INDEX,MIN	90
FLASH POINT, (COC) C,MIN	210
POUR POINT, C , MAX	0
SULPHATED ASH,%WT,MAX	2.6
TBN ,mgKOH/g,MIN	16
DB CORROSION TEST	
CORROSION RESISTANCE NUMBER, MIN	90
STAINING DISCOLOURATION, MAX	NONE

APPROVED BY:
M/s GUJRAT FORGINGS
M/s HM

PRESS TO
RETURN



FOR FURTHER INFORMATION PLEASE CONTACT OUR NEAREST
REGIONAL OFFICE