



HP Lubricants - Product Data Sheet



HP NATURAL GAS ENGINE OIL M 40

- HP NATURAL GAS ENGINE OIL M 40 IS MID ASH NATURAL GAS ENGINE OIL FOR STATIONARY APPLICATION
- OIL MEETS API-CF
- RECOMMENDED FOR STATIONARY DG SETS RUNNING ON SOUR GAS (LANDFILL & SEWAGE) REQUIRING MID ASH (0.6% WT TO 1% WT.)
- ALSO RECOMMENDED FOR SUPERIOR & LEAN BURN WAUKESHA ENGINES
 - GOOD CONTROL ON OXIDATION & NITRATION
 - EXCEPTIONAL CONTROL ON DEPOSITS & WEAR

KINEMATIC VISCOSITY cst @ 100 C	13.5-16.0
VISCOSITY INDEX,MIN	90
FLASH POINT, (COC) C,MIN	215
POUR POINT, C , MAX	-6
SULPHATED ASH,% WT,MAX	0.6-1.0
TBN ,mgKOH/g,MIN	7.5

**ENGINES RUNNING ON SOUR GAS REQUIRE A HIGH TBN ,
BECAUSE SOUR GAS ON COMBUSTION PRODUCE STRON
ACIDS**

**PRESS TO
RETURN**



**FOR FURTHER INFORMATION PLEASE CONTACT OUR NEAREST
REGIONAL OFFICE**